

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : B29C 65/36, B26B 19/38, A61C 17/26		A1	(11) International Publication Number: WO 00/24565
(21) International Application Number: PCT/EP99/07490		(43) International Publication Date: 4 May 2000 (04.05.00)	
(22) International Filing Date: 4 October 1999 (04.10.99)		(81) Designated States: CN, JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(30) Priority Data: 98203584.2 23 October 1998 (23.10.98) EP		Published With international search report.	
(71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).			
(72) Inventors: RIJZEN, Martinus, M.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). MEIJER, Matthijs, J.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).			
(74) Agent: BOS, Kornelis, S.; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).			
(54) Title: APPARATUS WITH A HOUSING PROVIDED WITH A SYNTHETIC RESIN WALL PORTION WITH A SYNTHETIC RESIN PANEL PROVIDED THEREON			
(57) Abstract			
<p>A housing (1) of an apparatus has a plastics wall portion (2) provided with a plastics panel (4). To make a reliable and visually acceptable connection of the panel (4) to the wall portion (2), the panel is fixed to the wall portion by means of an induction welding process. In this way the connection is resistant to chemical compounds like lotions. Therefore a metal element (8) of electric conducting material having the shape of a closed loop wire is inserted between the wall portion (2) and the panel (4) and subsequently an electromagnetic field is applied in close proximity to the element. Preferably such panel (4) can be used to cover an opening (11) in the wall portion (2) for a display (10) and/or a switch (15) function. To make the housing watertight the element (8) between the panel (4) and the wall portion (2) should surround the opening (3, 11).</p>			

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MT	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Apparatus with a housing provided with a synthetic resin wall portion with a synthetic resin panel provided thereon.

The invention relates to an apparatus, such as a shaver, a toothbrush, or a kitchen machine, with a housing which has a synthetic resin wall portion on which a synthetic resin panel is fastened.

5

It is often desirable for wall portions of a housing to be provided with panels. Such panels may have a decorative function, but also a technical function. Various methods are known for fastening such panels to a housing wall. Examples are screw connections and snap connections. If the panel is present at the outside of the wall portion, the
10 above methods do not lead to an attractive appearance. Snapping home in practice often gives rise to play, so that the panel will be slightly loose. Gluing is a better method in this case. Although there are satisfactory glue compositions nowadays, they are not resistant to chemical substances such as additives (lotions) in the long run. Another fastening method is ultrasonic welding. Here a vibratory force is applied to one of the parts by means of a tool. This often
15 causes damage to the surface of the wall, which is not acceptable visually. In addition, the choice of materials is limited in the case of ultrasonic welding, inter alia on account of the material characteristics.

20

It is an object of the invention to provide an apparatus in which a synthetic resin panel is fastened to a synthetic resin wall portion of a housing in a reliable and visually acceptable manner.

25

The invention is for this purpose characterized in that an element of electrically conducting material having the shape of a closed loop is present between the panel and the wall portion, by means of which element the panel is fastened to the wall portion through an RF (Radio Frequency) adhesion process.

In an RF (Radio Frequency) adhesion process, also called inductive welding, an electromagnetic field is generated close to the element, so that an induction current will flow through the element. The ohmic resistance of the element causes a heat generation in the element which melts the synthetic resin parts adjacent to the elements, whereupon these elements are fused together and fused to the element upon cooling down. Melting takes place through a small depth, so that no deformations are visible at the surface of the synthetic resin panel. It was found that this method leads to a reliable connection of the panel to the wall portion which is visually acceptable and is resistant to liquids, especially chemical liquids. An additional advantage of this method is that the element need not be plane but may also have a curved shape, adapted to the shape of the wall portion and the panel. This offers a designer a considerable freedom in design.

A preferred embodiment is characterized in that the synthetic resin housing is at least partly watertight, and the wall portion has at least one opening for accommodating electrical or mechanical elements, such as a display or a switch, while the panel is arranged over said opening and the element of electrically conducting material encircles the opening. If the synthetic resin wall portion of the housing is provided with an opening and the housing has to be watertight for cleaning purposes, the opening must also be closed in a watertight manner. The most well-known method for rendering the opening with a panel watertight is through the application of an elastic seal between the panel and the wall portion. The parts must then be fastened against one another with force, for example with screws. This is a good method in principle, but it is found in practice that the seal may lose its elasticity after a longer period, and thus its sealing effect, also through the action of chemical substances. Nowadays, the seal is integrally manufactured with one of the synthetic resin parts in the injection molding process. This leads to another problem if at least one of the parts is to be painted. The painting process must take place before electrical or mechanical components are fastened in or against the housing wall. It is not possible, however, to injection-mold a sealing to painted parts. As was mentioned earlier, a glue connection and ultrasonic welding also have their disadvantages. The joint obtained through inductive welding supplies a highly reliable seal.

A further embodiment is characterized in that the wall portion is provided with two openings, one opening for a display and the other opening for a switch, said openings being both covered at an inside of the wall portion by said panel, the latter being provided with a window of a transparent material situated in front of the display opening and with a membrane with an actuator situated in the opening for the switch.

A yet further embodiment is characterized in that a second panel is present which is fastened to the outside of the wall portion, again by means of an element of electrically conducting material in the shape of a closed loop and an RF adhesion process, which panel has an operational surface of a flexible material which lies opposite the
5 membrane with the actuator of the panel mentioned earlier, and which panel covers the opening in the wall portion in front of the switch.

The invention will now be explained in more detail with reference to an
10 example shown in a drawing, in which

Fig. 1 shows an electric shaver in perspective view,

Fig. 2 shows part of the shaver of Fig. 1, some parts being represented in
exploded view,

Fig. 3 is a cross-sectional view of part of the shaver of Fig. 1, and

15 Fig. 4 is a cross-sectional view of part of the shaver of Fig. 1 in a second embodiment.

The electric shaver has a housing 1 with a synthetic resin wall portion 2 in
20 which an opening 3 is present to accommodate a display function. The opening is closed off by means of a synthetic resin panel 4 which is fastened against the inside 5 of the wall portion 2. The panel 4 is for this purpose provided with a circumferential groove 6, while the inside of the wall portion is provided with a raised wall 7 which fits the groove 6. The raised wall and the groove together encircle the opening 3. Between the groove 6 and the raised wall 7 there is
25 an element 8 of an electrically conducting material which has the shape of a closed loop corresponding to the shape of the bottom of the groove 6. The element 8 is preferably made of brass because of its suitable resistivity value. Obviously, however, alternative materials are also possible. Upon the application of an electromagnetic field adjacent the element 6, a current will flow through this element causing a heat generation which melts the synthetic
30 resin parts of the groove 6 and of the raised wall 7, which parts will become fused together through cooling-down after the electromagnetic field has been removed. The element 8 remains fixed in its connection location. The panel 4 thus closes off the opening 3 in a watertight manner. The opening is designed for holding a display in this example. The panel 4 is for this purpose provided with a window 9 of a transparent material. Behind this window

there is an electronic component such as an LCD 10. The wall portion 2 is further provided with a second opening 11 designed for accommodating a switch. The covering panel 4 also covers this opening 11, i.e. the current-conducting element 8 between the groove 6 of the panel 4 and the raised wall 7 of the wall portion 2 also surrounds the opening 11. The panel 4 is provided with an opening 12 for a switch closed off in a watertight manner by a membrane 13. An actuator 14, by means of which a switch 15 is operated, for example for switching the apparatus on and off, is present in the center of the membrane. The actuator 14 may be molded together with the synthetic resin panel 4 in the injection molding process in the form of a thin, flexible synthetic resin strip 16. The actuator is passed through the opening 12. The opening 12 is covered at the outside 17 of the wall portion 2 by a second panel 18 which is also fastened to the wall portion 2 in an RF adhesion process. To this end, an element 19 of electrically conducting material and having the shape of a closed loop is applied between the panel 18 and the outside 17 of the wall portion 2. The panel 18 comprises two layers, i.e. a first layer 20, for example made of the same type of synthetic resin as the wall portion 2, and a second layer 21 of a flexible synthetic resin. The first layer 20 has an opening 22 covered by the flexible second layer at the area of the opening 11. The actuator 14 is present immediately behind the flexible layer 21. This portion of the flexible layer accordingly acts as an operational surface 23. Applying a pressure on the flexible operational surface presses down the actuator, which thus operates the switch 15. The panel 18 at the same time serves as a decorative panel. The flexible layer 21 in addition provides a secure grip when the apparatus is held.

In the second embodiment shown in Fig. 4, the membrane 13 extends into the opening 11 of the wall portion 2 and forms one integral whole with the operational surface 23 for the switch 15. The second panel 18 here only has a decorative function and the function of providing a secure grip thanks to the flexible layer 21.

The RF adhesion process, also called induction welding process, takes place at a low frequency, i.e. approximately 40 kHz. Nickel or brass is used as the material for the element 8, 19.

It will be obvious that the invention may also find an application in other apparatuses which must be watertight such as a toothbrush or a kitchen machine.

The elements 8, 19 need not lie in a flat plane, but they may also have a curved shape, such as the element 19. This means for a designer that he has a greater freedom in the choice of component shapes. The elements are simple and inexpensive stamping products. Much waste material is left after stamping, but this may be easily recycled.

CLAIMS:

1. An apparatus, such as a shaver, a toothbrush, or a kitchen machine, with a housing (1) which has a synthetic resin wall portion (2) on which a synthetic resin panel (4) is fastened, characterized in that an element (8) of electrically conducting material having the shape of a closed loop is present between the panel (4) and the wall portion (2), by means of which element (8) the panel (4) is fastened to the wall portion (2) in an RF adhesion process.
2. An apparatus as claimed in claim 1, characterized in that the housing (1) is at least partly watertight, and the wall portion (2) has at least one opening (3) for accommodating electrical or mechanical elements, such as a display or a switch, while the panel (4) is arranged over said opening (3) and the element (8) of electrically conducting material encircles the opening (3).
3. An apparatus as claimed in claim 2, characterized in that the panel has an opening which is closed off by a membrane (13), which membrane is provided with an actuator (14) which is present in the opening (11) for the switch (15).
4. An apparatus as claimed in claim 2, characterized in that the wall portion (2) is provided with two openings (3, 11), one opening (3) for a display and the other opening (11) for a switch, said openings (3, 11) being both covered at an inside (5) of the wall portion (2) by said panel (4), the latter being provided with a window (9) of a transparent material situated in front of the display opening (3) and with a membrane (13) with an actuator (14) situated in the opening (11) for the switch (15).
5. An apparatus as claimed in claim 4, characterized in that a second panel (18) is present which is fastened to the outside (17) of the wall portion (2), again by means of an element (19) of electrically conducting material in the shape of a closed loop and an RF adhesion process, which panel (18) has an operational surface (23) of a flexible material which lies opposite the membrane (13) with the actuator (14) of the panel (4) mentioned earlier, and which panel (18) covers the opening (11) for the switch (15) in the wall portion (2).

6. An apparatus as claimed in claim 1, characterized in that the RF adhesion process takes place at a frequency of between 30 kHz and 50 kHz.
7. An apparatus as claimed in claim 1, characterized in that the element (8) is
- 5 made of brass or nickel.




FIG. 1

2/4




FIG. 2

3/4




FIG. 3

4/4




FIG. 4

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/EP 99/07490

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B29C65/36 B26B19/38 A61C17/26

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B29C B26B A61C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 801 343 A (TAMBA SHINICHI ET AL) 31 January 1989 (1989-01-31) the whole document	1,2
A	EP 0 707 926 A (WAHL CLIPPER CORP) 24 April 1996 (1996-04-24) column 4, line 23 - column 5, line 29; figures 1,2	1
A	DE 43 19 615 A (BRAUN AG) 15 December 1994 (1994-12-15) column 9, line 38 - line 42; figure 10	3
A	US 4 491 970 A (LAWHITE ERIC L. ET AL) 1 January 1985 (1985-01-01) the whole document	1-3

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"S" document member of the same patent family

Date of the actual completion of the international search

29 December 1999

Date of mailing of the international search report

12/01/2000

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Palermitaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Herijgers, J

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/07490

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4801343 A	31-01-1989	JP 1626257 C	28-11-1991
		JP 2054777 B	22-11-1990
		JP 60217137 A	30-10-1985
EP 0707926 A	24-04-1996	US 5606799 A	04-03-1997
		AU 698924 B	12-11-1998
		AU 3049195 A	02-05-1996
		BR 9504490 A	20-05-1997
		CA 2157560 A	22-04-1996
		JP 8182871 A	16-07-1996
		ZA 9507515 A	28-03-1996
DE 4319615 A	15-12-1994	NONE	
US 4491970 A	01-01-1985	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.